

# **BLACKFRIAR PAINTS LTD**

## **TECHNICAL DATA SHEET**

### **BF052 Blackfriar Matt Black Paint.**

Revision  
date:  
05/01/07

<b><u>Product Information</u></b>	<b><u>Technical Spec</u></b>	<b><u>Recommended Spreading Rate</u></b>
<p><b><u>Description</u></b></p> <p>A multi purpose dead matt paint for interior metal and wood.</p>	<p><b><u>Composition</u></b></p> <p>Based on a blend of high quality alkyd resins and selected black pigments.</p>	<p>13m<sup>2</sup>/ltr</p>
<p><b><u>Usage/purpose</u></b></p> <p>Ideal for old beams, panelling, doors, ornamental iron work, stage scenery, darkrooms etc</p>	<p><b><u>Properties</u></b></p> <p>VOC Content: 392 gm/ litre.</p>	<p><b><u>Thinning</u></b></p> <p>Up to 10% with white spirit</p>
<p><b><u>Characteristics</u></b></p> <p>A high build smooth finish that is non reflective and protective.</p>	<p><b><u>Performance</u></b></p> <p>Primarily for use inside. May be used on small artefacts outside.</p>	<p><b><u>Drying Time</u></b></p> <p>Touch dry in 2-4 hours Recoatable after 16 hours under normal conditions (20°C 50% r/h).</p>
<p><b><u>Finish</u></b></p> <p>Dead Matt</p>	<p><b><u>Surface Preparation</u></b></p> <p>Ensure the substrate to be painted is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease etc). When using over metal remove all signs of rust to a clean bright surface and prime immediately On other substrates prime as necessary with the appropriate Blackfriar Primer.</p>	<p><b><u>Cleaning</u></b></p> <p>Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner</p>
<p><b><u>Colour(s)</u></b></p> <p>Black</p>	<p><b><u>Application Method</u></b></p> <p>Brush, Roller, Spray Ensure products are thoroughly stirred with a <b>broad</b> stirrer. This is especially important with matt paints. Apply a minimum of two full coats.</p>	<p><b><u>Limitations</u></b></p> <p>Matt paints are not as durable as satin/gloss paints when used outside. For larger exterior surfaces the use of Blackfriar Satin Black is strongly recommended.</p>
<p><b><u>Packaging</u></b></p> <p>125ml, 250ml, 500ml, 1litre, 2.5litre. Larger sizes may be available on request dependant on volume required</p>		<p><b><u>Environmental Info.</u></b></p> <p>Dangerous for the environment.</p>
<p><b><u>Disclaimer;</u></b> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p><b>For Technical Enquiries, Material Safety Data Sheets Telephone 0191 4106611</b></p>	<p>Paint Product UN No. 1263.</p>
		<p><b>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</b></p>